

Stadium Convergence

DSA Global Summit

Matt MacPherson Wireless CTO Cisco Networking Group



SoFi Stadium




SoFi Wi-Fi






Intuit Dome - Clippers




Intuit Dome - Wi-Fi 6E

Combined 6GHz Omni with 5GHz Directional



Wi-Fi 7 Determinism → 5/6G Convergence Ready



*from WTSN PoC CU - Channel Utilization

Directional AP/Antenna Selection Segmenting RF

AP/Antenna	Beamwidth	Approx. Distance
Integrated AP + Directional Antenna CW9166D1 (WiFi 6E) / Indoor Cloud- or On-Prem-managed	2.4: 70° 5GHz: 70° 5GHz XOR : 60° 6GHz: 60°	15'/5m - 30'/10m from AP to clients
Integrated AP + Directional Antenna CW9176D1 (WiFi 7) / Indoor Cloud- or On-Prem-managed	2.4: 80° 5GHz: 70° 6GHz: 70°	15'/5m - 30'/10m from AP to clients
Dual-Band "Wide" Patch Antenna AP: 9120AXE/P, 9130AXE Antenna: AIR-ANT2566P4W-R	2.4GHz: 105/70 ° 5GHz: 125/60°	< 30' / 10m from AP to clients
Integrated AP + Antenna: High Gain CW9179F / Indoor or Outdoor* Cloud- or On-Prem-managed	2.4GHz: 70° 5/6GHz: 70x35 (Wide) 5/6GHz: 35x35 (Narrow)	Primary overhead coverage (i.e. seating areas / conference halls; > 30'/10m, <200'/60m to clients

CISCO WIRELESS

Industry's first Wi-Fi 7 access point for large venues

Wi-Fi that reaches everywhere

Wi-Fi 7 speed and performance for everyone in the audience and more

Designed for every venue

Indoor/Outdoor, concourse-ready and multi-use all-in-one, integrated access point

Configurable and flexible installation

Comprehensive coverage to get the best value from your install

On-Prem or Cloud-Managed

One PID, flexible management options

4th-Generation Hyper-directional AP



CW9179F

CW9179F - Indoor & Outdoor Usage

Indoor Deployment / LPI Mode

Outdoor Deployment / SP Mode (with Environment Pack)






Environment Pack: Weatherizes & Signals to AP that it is Standard Power only

Performance Comparison: Overhead / Under-Seat



Under Seat / Omni



Time of event

Overhead/Directional

Red = High Co-Channel Interference (CCI) / Poor Performance

CW9179F: BottleRock (Napa Valley Music Festival)

Wi-Fi 7 + Standard Power + AFC + OpenRoaming













OpenRoaming

Converging Identity for Universal Access

Access





Guest & Public ANPs

Seamless onboarding of indoor users. Act on insights and extend business outcomes.

90% of our time is spent indoors

Federation







Identity





MNO & SP IDPs

Visibility of users when auth. on indoor networks. Delivering cost effective indoor coverage.

>85%

of mobile data is consumed indoors

Users/Things

Seamless and secure indoor connectivity.


Built-in privacy protection.

Mobile World Congress (MWC)

Fira de Barcelona

VENUES. Gran Via


- One of the newest, modern and more efficient
- Located at the business metropolitan área of BCN
- 240.000 m2 gross Surface
- 8 Halls, Convention Centers, Heliports, services and public transport





Mobile World Congress 2025 Barcelona

EU Limits Deployments to 480MHz in 6GHz Today



Always Available Mission Critical & Emergency

Hospital

+

Coffee Shop

✓ Wi-Fi AP

Library

Services

Through Converged Access!







Emergency Calling

Ability for a Wi-Fi capable device, without any conventional access network credentials, using native dialer make an emergency 911/112/* call over Wi-Fi.





National Security & Emergency Preparedness (NS/EP)

Wi-Fi APs granting prioritized access for NS/EP (e.g., first responders, and other emergency personnel) users during emergency situations.





2

Emergency Warning Systems

A system that delivers emergency alerts such as tsunami warnings, earthquake notifications, or AMBER alerts to Wi-Fi users.

Requirements



Network Access Using Emergency Passpoint Profile for Emergency Calling

- Access Network Supports Emergency Services
- Devices use Emergency Passpoint Profile for temporary access granted by a designated IDP
- Activate profile only when emergency is triggered
- Used in environments where there is no availability of public cellular networks



Location of the Caller

- Location signaling from ANP to IDP
- Caller Location Determination for PSAP Routing
- Detect of Rogue Callers & Prevent Location Spoofing
- Location signaling is optional for NS/EP



Authorization for Priority Access

 Authorization grant through service providercontrolled interface for NS/EP service



Location-based Alerts

- ANP registers with the PWS notification provider
- · ANP receives alerts with location metadata
- Alerts are delivered to the access points that match the location in the alert
- Access points then forward the alerts to users over Wi-Fi access.





based alerts


5G is the answer to Wi-Fi coverage

Wi-Fi is the answer to cost-effective 5G densification (capacity)

Convergence is the answer to wireless access for everyone & everything

_

Convergence is happening Now!



Thank you